



EVOLUTION®

THE ART OF QUALITY AND COLOR



Evolution's creamy consistency has been formulated to provide a thicker coat than typical wall paints and can often provide one-coat coverage, helping you to achieve your masterpiece with less effort. Use it in your home, office, or anywhere you want the rich color of the ColorEvolution collection to come through. Feel the luxurious craftsmanship in the rich, thick textures as you spread the art of paint on the canvas of your walls.



- Thick and creamy
- Less than 50 g/l VOC in all sheens
- Stain resistant
- Excellent splatter resistance
- Also available in a Door, Cabinet, and Trim formulation
- Washable



EVOLUTION®

THE ART OF QUALITY AND COLOR

PAPER

Our finest interior coating enhanced with Ceramic Technology for use on walls where a durable flat finish is desired. The matte finish offers the minimal light reflection of a flat with increased washability. Also a great choice or use on walls with uneven surfaces.

SILK

Our superior quality, thick & creamy, durable wall coating will minimize dirt pick-up and is washable. Ideal for projects where a deep, rich look and some sheen and washability are desired.

CANVAS

This extra-rich, luminescent, low-sheen texture will fill your life with soft, warm hues. Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. This unique product is easy to apply with low splatter and excellent flow and leveling properties.

GLASS

The finest semigloss wall coating we have ever created. The thick creamy texture reduces run and hardens to provide a smooth, durable sheen. It is an elegant choice for interior walls where extra durability is needed.

SPECIFICATIONS FOR EVOLUTION INTERIOR WALL FINISH

	PAPER	CANVAS	SILK	GLASS
Volume Solids	41.0%	43.4%	41.0%	37.0%
Viscosity	100-105 KU	100-105 KU	100-105 KU	105-105 KU
Weight Per Gallon	11.6#	11.8#	11.4#	10.4#
Gloss	<5%@85°	3-7%@85°	5-10%@85°	45-55%@85°
V.O.C. (minus water)	47.0 g/L	39.0 g/L	45.0 g/L	46.0 g/L

COVERAGE: Approximately 350-450 square feet per gallon @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface.

DRY TIME: One hour to touch and four hours to recoat @ 70°F and 50% relative humidity.

SPECIFICATIONS FOR EVOLUTION DOOR, CABINET, & TRIM FINISHES

	SATIN	SEMIGLOSS
Volume Solids	39.0%	37.0%
Viscosity	105-110 KU	105-105 KU
Weight Per Gallon	11.0#	10.4#
Gloss	10-20%@85°	45-55%@85°
V.O.C. (minus water)	48.0 g/L	49.0 g/L

COVERAGE: Approximately 350-450 square feet per gallon @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface.

DRY TIME: One hour to touch and two-four hours to recoat @ 70°F and 50% relative humidity.

ABOUT MILLER PAINT

Established in 1890, Miller Paint is an employee owned company with a proud Northwest tradition of creating products made for our unique Northwest climate. From our humble beginnings as a family-run company, to a company with over 300 employees and over 50 locations, Miller Paint has always been there for the professional and homeowner alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised.

Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR.
REV 9/16

